


## Sechskantmuttern DIN 6330 B

(Höhe 1.5 d)

Stahl, Güte 10, schwarz  
mit einseitig kugeligter Auflagefläche

d <sub>1</sub>	d <sub>2</sub>	e	m	r	s	 g
<b>M 6</b>	7,0	11,5	9	9,0	10	5
<b>M 8</b>	9,0	15,0	12	11,0	13	9
<b>M 10</b>	11,5	18,5	15	15,0	16	20
<b>M 12</b>	14,0	20,8	18	17,0	18	28
<b>M 14</b>	16,0	24,2	21	20,0	21	45
<b>M 16</b>	18,0	27,7	24	22,0	24	58
<b>M 18</b>	20,0	31,2	27	24,5	27	83
<b>M 20</b>	22,0	34,6	30	27,0	30	110
<b>M 22</b>	24,0	39,3	33	29,0	34	130
<b>M 24</b>	26,0	41,6	36	32,0	36	195
<b>M 30</b>	32,0	53,1	45	41,0	46	405
<b>M 36</b>	38,0	63,5	54	50,0	55	715

Kugelfläche passend zu Kegelpfannen DIN 6319. Mit dieser Kombination können nicht parallele Spannflächen ausgeglichen werden.


◀ **Nr. 10 108**

Bestellbeispiel

10108.BM08

d 1      M 08

**10**



Auch lieferbar in NIRO  
M 8 - M 10 - M 12 - M 16 - M 20.