



- 3 Form**
- R1** Rechtsgewinde, Wellenzapfen einseitig
  - R2\*** Rechtsgewinde, Wellenzapfen beidseitig
  - L1\*** Linksgewinde, Wellenzapfen einseitig
  - L2\*** Linksgewinde, Wellenzapfen beidseitig

1

2

d <sub>1</sub>	l <sub>1</sub> Hub (Verstellweg des Schlittens) Standardlängen					max. Hub	Gewinde- spindel	b	d <sub>2</sub>	d <sub>3</sub> **	d <sub>4</sub> ***	d <sub>5</sub>	d <sub>6</sub>	für Schraube DIN 912
18	100	150	200	250	420		TR10x3	28	6	-	M 5	5,3	-	-
30	100	150	200	300	1500		TR14x4	50	8	M 6	M 6	6,5	9	M 5
40	100	150	200	300	2650		TR20x4	60	12	M 8	M 8	8,5	13,5	M 6
50	100	150	200	300	2760		TR20x4	72	12	M 10	M 8	8,5	13,5	M 8
60	300	400	500	-	2740		TR25x5	80	14	M 10	M 10	10,5	13,5	M 8

d <sub>1</sub>	d <sub>7</sub>	für Schraube DIN 912	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub>	h <sub>5</sub>	l <sub>2</sub> Gesamt- länge	l <sub>3</sub>	l <sub>4</sub>	m <sub>1</sub>	m <sub>2</sub>	m <sub>3</sub>	m <sub>4</sub>
18	-	-	28	29	1	14,5	0,75	3xb+l <sub>1</sub>	81	16	2xb+l <sub>1</sub>	68	-	20
30	10,5	M 6	52	54	2	27	0,85	3xb+l <sub>1</sub>	130	16	2xb+l <sub>1</sub>	114	92	30
40	13,5	M 8	60	63	3	31,5	1,05	3xb+l <sub>1</sub>	180	17	2xb+l <sub>1</sub>	160	132	39
50	13,5	M 8	72	76	4	38	1,2	3xb+l <sub>1</sub>	206	18	2xb+l <sub>1</sub>	184	150	46
60	16,5	M 10	86	90	2	44	1,35	3xb+l <sub>1</sub>	240	19	2xb+l <sub>1</sub>	216	185	55

d <sub>1</sub>	m <sub>5</sub>	m <sub>6</sub>	m <sub>7</sub>	m <sub>8</sub>	m <sub>9</sub>	s Sechskant	Passfeder DIN 6885	Montage-Set	Stellungsanzeiger	Handrad	
18	-	20	18	-	4,5	8	A2x2x12	GN 491.1	GN 955	-	GN 923.18
30	35	30	42	9,5	12	10	A2x2x12	GN 491.1	GN 954	GN 9054	GN 923.30
40	38	39	62	12,5	12	13	A4x4x12	GN 491.1	GN 953	GN 9053	GN 923.40 / GN 924.40
50	50	46	62	13	15	13	A4x4x12	GN 491.1	GN 953	GN 9053	GN 924.50
60	60	55	74	14	16,5	17	A5x5x16	GN 491.1	GN 953	GN 9053	GN 924.60

\*\*\* nutzbare Gewindetiefe min. 1,5 x d<sub>4</sub> \*\* nutzbare Gewindetiefe beidseitig min. 2 x d<sub>3</sub> \* in der Regel nicht auf Lager