

## Muttern für T-Nuten Rhombus

Vergütungsstahl Güte 10, schwarz



Nr. 07 125

Bestellbeispiel

07125.M08X10

d Nennmaß M 08  
10



d	Nuten-nennmaß	a	e	h	k	g
M 6	8	7,6	13	10	6	5
M 8	10	9,6	15	12	6	9
M 10	12	11,6	18	14	7	11
M 12	14	13,6	22	16	8	20
M 14	16	15,6	25	18	9	30
M 16	18	17,6	28	20	10	45
M 18	20	19,6	32	24	12	70
M 20	22	21,6	35	28	14	95
M 24	28	27,6	44	36	18	215
M 30	36	35,5	54	44	22	430
M 36	42	41,5	65	52	26	690

## Schrauben für T-Nuten DIN 787

Vergütungsstahl geschmiedet  
Güte 8.8, schwarz,  
Nutenführung gefräst




Nr. 07 116

Bestellbeispiel

07116.M10X10X40

d 1 Nennmaß M 10  
10  
l 40



d <sub>1</sub>	Nu-tenmaß	l	a	b	e	k	g
M 6	6	25	5,6	15	10	4	8
M 6	6	40	5,6	28	10	4	10
M 6	6	63	5,6	40	10	4	14
M 8	8	32	7,6	22	13	6	19
M 8	8	50	7,6	35	13	6	24
M 8	8	80	7,6	50	13	6	34
M 10	10	40	9,6	30	15	6	33
M 10	10	63	9,6	45	15	6	44
M 10	10	100	9,6	60	15	6	62
M 12	12	50	11,6	35	18	7	58
M 12	12	63*	11,6	45	18	7	67
M 12	12	80	11,6	55	18	7	79
M 12	12	125	11,6	75	18	7	111
M 12	12	200	11,6	120	18	7	165
M 12	14	50	13,6	35	22	8	76
M 12	14	63*	13,6	45	22	8	85
M 12	14	80	13,6	55	22	8	97
M 12	14	125	13,6	75	22	8	129
M 12	14	200	13,6	120	22	8	183
M 16	16	63*	15,6	45	25	9	136
M 16	16	80*	15,6	55	25	9	159
M 16	16	100*	15,6	63	25	9	185
M 16	16	160*	15,6	100	25	9	264
M 16	16	200*	15,6	125	25	9	311
M 16	16	250*	15,6	150	25	9	381
M 16	18	63	17,6	45	28	10	162
M 16	18	80*	17,6	55	28	10	184
M 16	18	100	17,6	63	28	10	210
M 16	18	160	17,6	100	28	10	290
M 16	18	200*	17,6	125	28	10	342

d <sub>1</sub>	Nu-tenmaß	l	a	b	e	k	g
M 16	18	250	17,6	150	28	10	408
M 20	20	80*	19,6	55	32	12	279
M 20	20	100*	19,6	65	32	12	320
M 20	20	125*	19,6	85	32	12	372
M 20	20	160*	19,6	100	32	12	444
M 20	20	200*	19,6	125	32	12	527
M 20	20	250*	19,6	150	32	12	630
M 20	20	315*	19,6	190	32	12	759
M 20	22	80	21,6	55	35	14	332
M 20	22	100*	21,6	65	35	14	373
M 20	22	125	21,6	85	35	14	425
M 20	22	160*	21,6	100	35	14	497
M 20	22	200	21,6	125	35	14	580
M 20	22	250*	21,6	150	35	14	674
M 20	22	315	21,6	190	35	14	807
M 24	28	100	27,6	70	44	18	642
M 24	28	125*	27,6	85	44	18	717
M 24	28	160	27,6	110	44	18	818
M 24	28	200*	27,6	125	44	18	937
M 24	28	250	27,6	150	44	18	1130
M 24	28	315	27,6	190	44	18	1275
M 24	28	400*	27,6	240	44	18	1532
M 30	36	125	35,5	80	54	22	1238
M 30	36	200	35,5	135	54	22	1556
M 30	36	315	35,5	200	54	22	2068
M 30	36	500	35,5	300	54	22	3125
M 36	42	160	41,5	100	65	26	2181
M 36	42	250	41,5	175	65	26	3000
M 36	42	400	41,5	250	65	26	3910
M 36	42	600*	41,5	340	65	26	5500

Bitte bei Bestellungen angeben, wenn die Schrauben für T-Nuten mit Mutter DIN 6330 und Scheibe DIN 6340 gewünscht werden.

komplett



Die mit \* versehenen Abmessungen sind in der DIN nicht enthalten.