

Einstellmaß für Bügelmessschrauben 0898



Ausführung

- Stab
- Spezialstahl
- Messflächen gehärtet
- Toleranzfeld JS 2
- Handwärmeschutz
- Messflächen planparallel geläpft
- Verpackung: einzeln verpackt

			Messbereich mm	Ø mm	Best. Nr.
▪			25	6,5	0898 101
▪			50	6,5	0898 102
▪			75	6,5	0898 103
▪			100	6,5	0898 104
▪			125	6,5	0898 105
▪			150	6,5	0898 106
▪			175	6,5	0898 107
▪			200	6,5	0898 108
▪			225	6,5	0898 109
▪			250	6,5	0898 110
▪			275	6,5	0898 111
▪			300	10,0	0898 112
▪			325	10,0	0898 113
▪			350	10,0	0898 114
▪			375	10,0	0898 115
▪			400	10,0	0898 116
▪			425	10,0	0898 117
▪			450	10,0	0898 118
▪			475	10,0	0898 119
▪			500	10,0	0898 120
			525	10,0	0898 121
			550	10,0	0898 122
			575	10,0	0898 123
			600	10,0	0898 124
			625	10,0	0898 125
			650	10,0	0898 126
			675	10,0	0898 127
			700	10,0	0898 128
			725	10,0	0898 129
			750	10,0	0898 130
			775	10,0	0898 131
			800	10,0	0898 132
			825	10,0	0898 133
			850	10,0	0898 134
			875	10,0	0898 135
			900	10,0	0898 136
			925	10,0	0898 137
			950	10,0	0898 138
			975	10,0	0898 139
			1000	10,0	0898 140
		▪	1050	10,0	0898 142
		▪	1150	10,0	0898 146
		▪	1250	10,0	0898 150
		▪	1350	10,0	0898 154
		▪	1450	10,0	0898 158
		▪	1550	10,0	0898 162
		▪	1650	10,0	0898 166
		▪	1750	10,0	0898 170
		▪	1850	10,0	0898 174
		▪	1950	10,0	0898 178

= QuickLock = QuickStart = Waterproof nach IP = Datenausgang = DIN