

Schwingmetall-Puffer einseitig Innengewinde

**Ausführung: Gummi
Naturkautschuk**

**Härte (Shore $\pm 5^\circ$): weich 40,
mittel 55, hart 70**

**Metallteile verzinkt, CRVI-frei,
Gummi aufvulkanisiert.**

Edelstahl auf Anfrage lieferbar




Nr. 27 004

Bestellbeispiel

27004.30-25-M8-55

**d 30
h 25
g M8
Härte 55**



d	h	g	l2
10	10	M4	4
10	15	M4	4
15	15	M4	5
20	10	M6	6
20	11	M6	6
20	15	M6	6
20	20	M6	6
20	25	M6	6
25	10	M6	6
25	15	M6	6
25	20	M6	6
25	25	M6	6
25	30	M6	6
30	15	M8	8
30	17	M8	8
30	20	M8	8
30	25	M8	8
30	30	M8	8
40	20	M8	8
40	25	M8	8
40	30	M8	8
40	30	M10	10
40	40	M8	8

d	h	g	l2
50	20	M10	10
50	30	M10	10
50	40	M10	10
50	45	M10	10
50	50	M10	10
60	40	M10	10
60	40	M12	12
70	45	M10	10
75	25	M12	12
75	40	M12	12
75	50	M12	12
75	55	M12	12
100	40	M16	16
100	50	M16	16
100	55	M16	16
100	60	M16	16
100	75	M16	16
150	45	M16	16
150	50	M16	16
150	55	M16	16
150	60	M16	16
150	75	M16	16