




# Mitnehmersteine, DIN-2079, legierter Einsatzstahl



Form A



Form B



Form C

## Mitnehmersteine DIN 2079

legierter Einsatzstahl,  
einsatzgehärtet, brüniert,  
geschliffen




Nr. 07 120

Bestellbeispiel

07120.A30

Form A  
Spindelkopf 30

Ausführung	Spindel- kopf Nr.	k	b <sub>2</sub> h <sub>5</sub>	d <sub>7</sub>	d <sub>8</sub>	g	h	l <sub>5</sub>	zugehörige Schraube DIN 912	 g
für Spindelköpfe Nr. 30 bis 60	<b>30</b>	16,5	15,9	6,4	10,4	6,2	16,0	-	M 6 x 16	25
	<b>40</b>	19,5	15,9	6,4	10,4	6,2	16,0	-	M 6 x 16	32
<b>Form A</b>	<b>45</b>	19,5	19,0	8,4	13,5	8,3	19,0	-	M 8 x 20	35
	<b>50-55</b>	26,5	25,4	13,0	19,0	12,3	25,0	-	M 12 x 25	85
	<b>60</b>	45,5	25,4	13,0	19,0	12,3	25,0	-	M 12 x 25	185
für Spindelkopf Nr. 60	<b>60</b>	45,5	25,4	13,0	19,0	12,3	25,0	-	M 12 x 25	140
<b>Form B</b>										
für Spindelköpfe Nr. 30 bis 50	<b>30</b>	13,5	15,9	6,4	10,4	6,2	24,5	5,5	M 6 x 25	31
	<b>40</b>	16,5	15,9	6,4	10,4	6,2	24,5	7,0	M 6 x 25	41
<b>Form C</b>	<b>45</b>	17,5	19,0	8,4	13,5	10,0	26,0	7,5	M 8 x 25	44
	<b>50</b>	24,0	25,4	13,0	19,0	12,3	29,0	11,0	M 12 x 30	89

