


Form A



Paßfedern DIN 6885 A aus Keilstahl C 45 entspricht St 60 K

Form A: rundstirnig



Nr. 07 118

Bestellbeispiel

07118.A10X8X40

Form A
b 10
h 8
Länge 40

Größe b x h mm	Längen* mm													
2 x 2	6	8	10	12	14	16	18	20	22	25	28	30	32	36
3 x 3	6	8	10	12	14	16	18	20	22	25	28	32	36	
4 x 4	8	10	12	14	16	18	20	22	25	28	32	36	40	45
5 x 3	12	14	16	18	20	22	25	28	32	36	40	45	50	56
5 x 5	12	14	16	18	20	22	25	28	32	36	40	45	50	56
6 x 4	16	18	20	22	25	28	32	36	40	45	50	56	63	70
6 x 6	16	18	20	22	25	28	32	36	40	45	50	56	63	70
8 x 5	20	22	25	28	32	36	40	45	50	56	63	70	80	90
8 x 7	20	22	25	28	32	36	40	45	50	56	63	70	80	90
10 x 6	25	28	32	36	40	45	50	56	63	70	80	90	100	110
10 x 8	25	28	32	36	40	45	50	56	63	70	80	90	100	110
12 x 6	32	36	40	45	50	56	63	70	80	90	100	110	125	140
12 x 8	32	36	40	45	50	56	63	70	80	90	100	110	125	140
14 x 6	40	45	50	56	63	70	80	90	100	110	125	140	160	
14 x 9	40	45	50	56	63	70	80	90	100	110	125	140	160	
16 x 7	45	50	56	63	70	80	90	100	110	125	140	160	180	
16 x 10	45	50	56	63	70	80	90	100	110	125	140	160	180	
18 x 7	50	56	63	70	80	90	100	110	125	140	160	180	200	
18 x 11	50	56	63	70	80	90	100	110	125	140	160	180	200	
20 x 8	56	63	70	80	90	100	110	125	140	160	180	200		
20 x 12	56	63	70	80	90	100	110	125	140	160	180	200		
22 x 9	63	70	80	90	100	110	125	140	160	180	200	220	250	
22 x 14	63	70	80	90	100	110	125	140	160	180	200	220	250	
25 x 9	70	80	90	100	110	125	140	160	180	200	220	250	280	
25 x 14	70	80	90	100	110	125	140	160	180	200	220	250	280	
28 x 10	80	90	100	110	125	140	160	180	200	220	250	280	320	
28 x 16	80	90	100	110	125	140	160	180	200	220	250	280	320	
32 x 11	90	100	110	125	140	160	180	200	220	250	280	320	360	
32 x 18	90	100	110	125	140	160	180	200	220	250	280	320	360	
36 x 12	100	110	125	140	160	180	200	220	250	280	320	360	400	
36 x 20	100	110	125	140	160	180	200	220	250	280	320	360	400	
40 x 14	110	125	140	160	180	200	220	250	280	320	360	400		
40 x 22	110	125	140	160	180	200	220	250	280	320	360	400		
45 x 16	120	140	160	180	200	220	250	280	320	360	400			
45 x 25	120	140	160	180	200	220	250	280	320	360	400			

* Bei Bestellung bitte angeben.



Wir führen auch:



Paßfedern F DIN 6885
ab 12 x 8 mit Bohrungen
für Abdruckschrauben




Paßfedern G DIN 6885
mit Schrägung




Paßfedern H DIN 6885
mit Schrägung

Nr. 07 127



Nasenflachkeil DIN 6884
Nasenkeil DIN 6887

Nr. 07 126



Scheibefedern DIN 6888