

Steckschlüssel (Rohr-Steckschlüssel) DIN-896 Form B - ISO-2236 / ISO-1085



Doppelseitiger Rohrsteckschlüssel

DIN 896 Form B - ISO 2236/ISO 1085

aus nahtlos kaltgezogenem Präzisions-
stahlrohr, gehärtet, vernickelt,
Verwendung mit Drehstift





Nr. 12 121

Bestellbeispiel:

12121.06X07

mm

6 x 7

mm	Drehstift Ø	<L>	 g	mm	Drehstift Ø	<L>	 g
6 x 7	5	100	30	18 x 19	12	160	195
7 x 8	6	100	30	19 x 22	12	165	220
8 x 9	6	105	35	20 x 22	12	165	220
8 x 10	6	120	45	21 x 23	14	170	225
9 x 10	6	120	45	19 x 24	14	185	300
9 x 11	6	120	55	22 x 24	14	185	300
10 x 11	6	120	55	24 x 26	14	185	300
10 x 13	6	120	80	24 x 27	14	185	300
11 x 13	8	135	85	24 x 30	16	205	380
12 x 13	8	135	85	25 x 28	16	205	350
12 x 14	8	140	85	27 x 30	16	205	380
13 x 15	8	140	90	30 x 32	16	205	410
13 x 16	8	140	90	30 x 34	16	205	500
14 x 15	8	140	90	30 x 36	18	220	530
13 x 17	10	150	130	32 x 36	18	220	530
14 x 17	10	150	130	36 x 41	18	220	700
16 x 17	10	150	130	41 x 46	18	245	800
16 x 18	10	150	135	46 x 50	18	250	1250
17 x 19	12	160	195	50 x 55	18	250	1670