

Fortsetzung von vorheriger Seite

EH 22630.

Aufnahme- bolzen

mit Kugelansatz

Best.-Nr. Stahl	Best.-Nr. Rostfreier Stahl	Ausführung	d ₁ g6	d ₂ n6	d ₃ -0,01 -0,05	d ₄	l ₁	l ₂	l ₃	t	r	b	g
22630.0508	22630.0568	Kugelansatz	8	8	8	M 3	10	8	2,0	6	2,0	–	6
22630.0510	22630.0570	voll,	10	10	10	M 3	13	10	2,5	6	2,5	–	12
22630.0512	22630.0572	nicht abgesetzt	12	12	12	M 4	15	12	3,0	8	3,0	–	21
22630.0516	22630.0576	(Bild 3)	16	16	16	M 5	20	16	4,0	10	4,0	–	51
22630.0520	22630.0580		20	20	20	M 5	25	20	5,0	10	5,0	–	101
22630.0525	–		25	25	25	M 5	25	25	6,0	10	6,0	–	176
22630.0530	–		30	30	30	M 6	30	30	8,0	12	8,0	–	307
22630.0540	–		40	40	40	M 6	40	40	10,0	12	10,0	–	729
22630.0550	–		50	50	50	M 6	50	50	12,0	12	12,0	–	1422
22630.0608	22630.0668	Kugelansatz	8	8	8	M 3	10	8	2,0	6	2,0	1,9	5
22630.0610	22630.0670	abgeflacht,	10	10	10	M 3	13	10	2,5	6	2,5	2,5	11
22630.0612	22630.0672	nicht abgesetzt	12	12	12	M 4	15	12	3,0	8	3,0	2,5	17
22630.0616	22630.0676	(Bild 4)	16	16	16	M 5	20	16	4,0	10	4,0	4,3	44
22630.0620	22630.0680		20	20	20	M 5	25	20	5,0	10	5,0	5,0	88
22630.0625	–		25	25	25	M 5	25	25	6,0	10	6,0	5,6	149
22630.0630	–		30	30	30	M 6	30	30	8,0	12	8,0	8,8	270
22630.0640	–		40	40	40	M 6	40	40	10,0	12	10,0	12,8	657
22630.0650	–		50	50	50	M 6	50	50	12,0	12	12,0	16,7	1243

