



## GN 345 / GN 345.5, Gelenkfüße, Fuß Kunststoff / mit 2 Befestigungsbohrungen









ELESA original design LV.F



## Form

- A ohne Mutter,
- ohne Gummiauflage **B** mit Mutter,
- ohne Gummiauflage **AG** ohne Mutter,
- mit Gummiauflage
- **BG** mit Mutter, mit Gummiauflage

Ų	2	3											
d <sub>1</sub>	d <sub>2</sub>	I <sub>1</sub>				l <sub>2</sub>	I <sub>3</sub>	I <sub>4</sub>	d <sub>3</sub>	k	sw	Kugel-Ø	Statische Belast- barkeit in kN (siehe Hinweis)
80	M 8	43	68	-	-	33	23	24	8,5	54	14	14	16
80	M 10	43	68	98	-	33	23	24	8,5	54	14	14	16
80	M 12	43	68	98	-	33	23	24	8,5	54	14	14	16
80	M 14	68	98	148	-	33	23	24	8,5	54	14	14	16
80	M 16	68	108	148	168	33	23	24	8,5	54	16	14	16
80	M 16	58	98	138	158	43	23	24	8,5	54	24	24	18
80	M 20	98	138	158	198	43	23	24	8,5	54	24	24	18
80	M 24	98	138	158	198	43	23	24	8,5	54	24	24	18
100	M 8	43	68	-	-	33	23	24	12,5	70	14	14	18
100	M 10	43	68	98	-	33	23	24	12,5	70	14	14	18
100	M 12	43	68	98	-	33	23	24	12,5	70	14	14	18
100	M 14	68	98	148	-	33	23	24	12,5	70	14	14	18
100	M 16	68	108	148	168	33	23	24	12,5	70	16	14	18
100	M 16	58	98	138	158	43	23	24	12,5	70	24	24	25
100	M 20	98	138	158	198	43	23	24	12,5	70	24	24	25
100	M 24	98	138	158	198	43	23	24	12,5	70	24	24	25
125	M 20	98	138	158	198	67	23	46	12,5	95	24	24	28
125	M 16	58	98	138	158	67	23	46	12,5	95	24	24	28
125	M 24	98	138	158	198	67	23	46	12,5	95	24	24	28