

Splintbolzen DIN 1434

Scheibe DIN 433

Splint DIN 94

Splintbolzen DIN 1434

mit Scheibe und Splint
9 S Mn Pb 28 K

-00 blank, geölt

Weitere Ausführungen:
-05 blau verzinkt
-10 gelb verzinkt
-15 phosphatiert

◀ **Nr. 09 131**

Bestellbeispiel
09131.4-00

d 1 4
blank geölt -00

Gabelkopf Größe	d ₁ h11	l ₂	Scheibe DIN 433 d	Splint DIN 94 s x l
4 x 8/16	4	9,2	4,3	1,0 x 10
5 x 10/20	5	12,0	5,3	1,6 x 10
6 x 12/24	6	14,5	6,4	1,6 x 10
8 x 16/32	8	18,7	8,4	2,0 x 16
10 x 20/40	10	23,2	10,5	3,2 x 20
12 x 24/48	12	28,2	13	4,0 x 32
14 x 28/56	14	31,2	15	4,0 x 32
16 x 32/64	16	36,2	17	4,0 x 32
18 x 36	18	44,0	19	4,0 x 32
20 x 40	20	47,0	21	4,0 x 32
25 x 50	25	59,0	25	6,3 x 63
28 x 56	28	63,5	28	6,3 x 63
30 x 60	30	67,0	30	6,3 x 63
36 x 72	35	76,0	36	8,0 x 63
42 x 84	42	94,0	42	8,0 x 63

ES-Bolzen

ES-Norm 01

Feder: Federstahl gehärtet und angelassen
Bolzen: 9S Mn Pb 28 K

-00 blank, geölt

Weitere Ausführungen:
-05 blau verzinkt
-10 gelb verzinkt
-15 phosphatiert

◀ **Nr. 09 132**

Bestellbeispiel
09132.10X20-05

Größe 10X20
blau verzinkt -05

Gabelkopf Größe	b	d ₁ h11	l ₁ ≈	l ₅ ≈	l ₆	g
4 x 8	11,0	4	18,5	15	9	1,6
5 x 10	13,5	5	23	19	12	2,7
5 x 20	13,5	5	33	29	12	2,9
6 x 12	16,0	6	28	23	14	4,6
6 x 24	16,0	6	40	35	14	5,0
8 x 16	21,5	8	37	31	19	10,4
8 x 32	21,5	8	52	47	19	11,5
10 x 20	26	10	45	39	23	19,0
10 x 40	26	10	65	59	23	21,0
12 x 24	31	12	53	47	28	34,0
12 x 48	31	12	78	69	28	34,5
14 x 28	34	14	62	52	31	45,0
14 x 56	34	14	91	82	31	50,0
16 x 32	39	16	73	62	36	70,0
16 x 64	39	16	103	92	36	71,5
20 x 40	40	20	88	71	49	132,0