



EH 24530.

Zylindergriffe

drehbar



Werkstoff:

Zylindergriff: • Duroplast PF 31, schwarz
• 24530.0008 - Thermoplast PA, schwarz, matt

Achsteil: • Stahl, galvanisch verzinkt
• Rostfreier Stahl 1.4305

Hinweis:

Temperatureinsatzbereich bis max. 110 °C, bei Thermoplast PA bis max. 80 °C.

Best.-Nr. Stahl	Best.-Nr. Rostfreier Stahl	d ₁	d ₂	d ₃	d ₄	l ₁	l ₂	l ₃	SW	g
24530.0008	-	14	M 6	8	11	28	10	0,5	3	13
24530.0010	24530.0210	18	M 6	10	15	40	12	2,5	3	29
24530.0020	24530.0220	21	M 6	10	17	50	13	2,5	3	42
24530.0021	-	21	M 8	10	17	50	13	2,5	4	43
24530.0030	-	22	M 6	10	18	56	13	2,5	3	47
24530.0031	-	22	M 8	10	18	56	13	2,5	4	48
24530.0040	24530.0240	23	M 8	13	19	65	14	2,5	4	79
24530.0041	-	23	M 10	13	19	65	14	2,5	5	80
24530.0050	-	26	M 8	13	21	80	16	2,5	4	106
24530.0051	24530.0251	26	M 10	13	21	80	16	2,5	5	108
24530.0060	24530.0260	28	M 10	13	22	90	16	2,5	5	126
24530.0071	24530.0271	31	M 12	14	25	102	20	2,5	6	178

