

Fortsetzung von vorheriger Seite

**EH 22370. /
EH 22380.**

**Kugelsperr-
bolzen**

**selbstsichernd,
mit elastischem Griff**

Best.-Nr. Rostfreier Stahl 1.4305	Best.-Nr. Rostfreier Stahl 1.4542, ausscheidungs- gehärtet	d ₁	l ₁	d ₂	d ₃	d ₄	l ₂	l ₃	l ₄	Aufnahme- bohrung H11	Scherfestigkeit zweischnittig kN min. 1.4305*	Scherfestigkeit zweischnittig kN min. 1.4542*	g
22370.0765	22380.0765	12	25	14,5	49	21,2	10,6	40,5	24,8	12	87	144	54
22370.0766	22380.0766	12	30	14,5	49	21,2	10,6	40,5	24,8	12	87	144	59
22370.0767	22380.0767	12	35	14,5	49	21,2	10,6	40,5	24,8	12	87	144	63
22370.0768	22380.0768	12	40	14,5	49	21,2	10,6	40,5	24,8	12	87	144	67
22370.0769	22380.0769	12	45	14,5	49	21,2	10,6	40,5	24,8	12	87	144	71
22370.0770	22380.0770	12	50	14,5	49	21,2	10,6	40,5	24,8	12	87	144	75
22370.0772	22380.0772	12	60	14,5	49	21,2	10,6	40,5	24,8	12	87	144	84
22370.0774	22380.0774	12	70	14,5	49	21,2	10,6	40,5	24,8	12	87	144	93
22370.0776	22380.0776	12	80	14,5	49	21,2	10,6	40,5	24,8	12	87	144	101
22370.0786	22380.0786	16	30	19,0	49	21,2	14,0	40,5	24,8	16	155	257	91
22370.0787	22380.0787	16	35	19,0	49	21,2	14,0	40,5	24,8	16	155	257	98
22370.0788	22380.0788	16	40	19,0	49	21,2	14,0	40,5	24,8	16	155	257	106
22370.0789	22380.0789	16	45	19,0	49	21,2	14,0	40,5	24,8	16	155	257	114
22370.0790	22380.0790	16	50	19,0	49	21,2	14,0	40,5	24,8	16	155	257	121
22370.0792	22380.0792	16	60	19,0	49	21,2	14,0	40,5	24,8	16	155	257	137
22370.0794	22380.0794	16	70	19,0	49	21,2	14,0	40,5	24,8	16	155	257	152
22370.0796	22380.0796	16	80	19,0	49	21,2	14,0	40,5	24,8	16	155	257	167

* Scherfestigkeit ähnlich DIN 50141

