

Fortsetzung von vorheriger Seite

EH 23050.

Best.-Nr. Rostfreier Stahl 1.4305	Best.-Nr. Rostfreier Stahl A4	Ausführung	d ₂ H13	d ₄	d ₅	h ₃	für Bolzen d ₆	Belastbarkeit bei statischer Belastung max. kN	Drehmoment für Schraubver- bindungen max. Nm*	ϒ _g
23050.0406	23050.0666	Kegelpfannen	7,1	12	11,0	2,8	6	6	6	1,4
23050.0408	23050.0668	aus	9,6	17	14,5	3,5	8	12	16	3,8
23050.0410	23050.0670	rostfreiem Stahl,	12,0	21	18,5	4,2	10	16	32	6,5
23050.0412	23050.0672	Form D	14,2	24	20,0	5,0	12	24	56	11,0
23050.0416	23050.0676	(Bild 2)	19,0	30	26,0	6,2	16	45	135	19,0
23050.0420	23050.0680		23,2	36	31,0	7,5	20	71	280	32,0
23050.0424	23050.0684		28,0	44	37,0	9,5	24	105	455	63,0
23050.0430	23050.0686		35,0	56	49,0	12,0	30	191	1050	127,0
23050.0436	23050.0688		42,0	68	60,0	15,0	36	–	–	234,0
23050.0442	23050.0692		49,0	78	70,0	18,0	42	–	–	362,0
23050.0448	23050.0694		56,0	92	82,0	22,0	48	–	–	642,0
23050.0466	23050.0706	Kegelpfannen	7,1	17	11,0	4,0	6	6	6	5,8
23050.0468	23050.0708	aus	9,6	24	14,5	5,0	8	12	16	15,0
23050.0470	23050.0710	rostfreiem Stahl,	12,0	30	18,5	5,0	10	16	32	22,0
23050.0472	23050.0712	Form G	14,2	36	20,0	6,0	12	24	56	40,0
23050.0476	23050.0716	(Bild 3)	19,0	44	26,0	7,0	16	45	135	66,0
23050.0480	23050.0720		23,2	50	31,0	8,0	20	71	280	95,0
23050.0484	23050.0724		28,0	60	37,0	10,0	24	105	455	171,0
23050.0490	23050.0730		35,0	68	49,0	12,0	30	191	1050	236,0

* Drehmomentangaben für Schrauben A2-70 können nur als sehr grobe und unverbindliche Richtwerte verstanden werden. Gegebenenfalls Vorlast berücksichtigen, Reibungszahl μ_{ges} 0,12.

Kugelscheiben Kegelpfannen

ähnlich DIN 6319

Rostfreier Stahl

