



4 Form (Fußsteller)

- D0** ohne Gummiauflage
- B0** ohne Gummiauflage, mit 2 Befestigungsbohrungen
- D1** mit Gummiauflage, aufgeklipst, schwarz
- D3** mit Gummiauflage, aufvulkanisiert, schwarz

| d ₁ | d ₂ | 1 | | | | 2 | | | | |
|----------------|----------------|-------------------|----|-----|-----|-------------------|-----|-----|-----|-----|
| | | Ausführung S / SK | | | | Ausführung T / TK | | | | |
| 40 | M 8 | 40 | 50 | 63 | - | - | - | - | - | - |
| 40 | M 10 | 50 | 60 | 80 | 100 | - | - | - | - | - |
| 40 | M 12 | 60 | 80 | 100 | 125 | - | - | - | - | - |
| 40* | M 16 | - | - | - | - | 75 | 100 | 125 | 150 | 200 |
| 50 | M 8 | 40 | 50 | 63 | - | - | - | - | - | - |
| 50 | M 10 | 50 | 60 | 80 | 100 | - | - | - | - | - |
| 50 | M 12 | 60 | 80 | 100 | 125 | - | - | - | - | - |
| 50 | M 16 | - | - | - | - | 75 | 100 | 125 | 150 | 200 |
| 60 | M 8 | 40 | 50 | 63 | - | - | - | - | - | - |
| 60 | M 10 | 50 | 60 | 80 | 100 | - | - | - | - | - |
| 60 | M 12 | 60 | 80 | 100 | 125 | - | - | - | - | - |
| 60 | M 16 | - | - | - | - | 75 | 100 | 125 | 150 | 200 |
| 80 | M 8 | 40 | 50 | 63 | - | - | - | - | - | - |
| 80 | M 10 | 50 | 60 | 80 | 100 | - | - | - | - | - |
| 80 | M 12 | 60 | 80 | 100 | 125 | - | - | - | - | - |
| 80 | M 16 | - | - | - | - | 75 | 100 | 125 | 150 | 200 |
| 80 | M 20 | - | - | - | - | 75 | 100 | 125 | 150 | 200 |
| 80 | M 24 | - | - | - | - | 100 | 125 | 150 | 200 | - |

* nicht lieferbar in Form B0