



EH 24591.

Handräder

ähnlich DIN 950

Rostfreier Stahl



Werkstoff:

Handrad:

- Rostfreier Stahl A4
- Sauber entgratet
- Nabe bearbeitet
- Kranz poliert

Ballengriff: • Rostfreier Stahl A4

Best.-Nr.	Ausführung	d ₁	d ₂ H9	d ₃	l ₁	l ₂	Anzahl der Arme	Ballen- griff Ø	⊘ g
24591.0005	ohne Nabennut,	100	10	25,5	17	14,5	3	–	431
24591.0010	ohne Griff,	125	12	27,0	18	15,8	3	–	655
24591.0015	Form B-F/A	140	14	29,0	19	17,0	3	–	851
24591.0020	(alt: A 4)	160	14	31,0	20	17,5	3	–	1112
24591.0030		200	18	37,0	24	20,0	3	–	1877
24591.0105	mit Nabennut,	100	10	25,5	17	14,5	3	–	434
24591.0110	ohne Griff,	125	12	27,0	18	15,8	3	–	659
24591.0115	Form N-F/A	140	14	29,0	19	17,0	3	–	854
24591.0120	(alt: A 3)	160	14	31,0	20	17,5	3	–	1115
24591.0130		200	18	37,0	24	20,0	3	–	1882
24591.0405	ohne Nabennut,	100	10	25,5	17	14,5	3	16	472
24591.0410	mit festem Griff, montiert,	125	12	27,0	18	15,8	3	20	748
24591.0415	Form B-F/G	140	14	29,0	19	17,0	3	20	939
24591.0420	(alt: F 4)	160	14	31,0	20	17,5	3	25	1273
24591.0430		200	18	37,0	24	20,0	3	25	2044
24591.0505	mit Nabennut,	100	10	25,5	17	14,5	3	16	473
24591.0510	mit festem Griff, montiert,	125	12	27,0	18	15,8	3	20	753
24591.0515	Form N-F/G	140	14	29,0	19	17,0	3	20	939
24591.0520	(alt: F 3)	160	14	31,0	20	17,5	3	25	1282
24591.0530		200	18	37,0	24	20,0	3	25	2049

Nabennuten DIN 6885 Blatt 1

d ₂	10,0	12,0	14,0	18,0
b ₃	3,0	4,0	5,0	6,0
t	11,4	13,8	16,3	20,8