



2 Form

- B** offener Spannarm, mit 2 Flankenscheiben
- BC** offener Spannarm, mit 2 Flankenscheiben und Andrückschraube GN 708.1
- F** massiver Spannarm, mit Halteschelle zum Anschweißen

1

Größe		F _H in N	a ≈	b ₁	b ₂	b ₃	b ₄	d ₁	d ₂ ≈	h ₁ ≈	h ₂	h ₃	h ₄	h ₅ max.
Stahl	Edelstahl	Haltekraft												
75	75	750	20	29	8	4	5,2	M 5	4,5	109	32	11	19	17
130	130	1050	28	35	10	5	6,2	M 6	5,5	156	41,5	16	25,5	25
230	230	2000	40	43	12	6	8,5	M 8	6,5	183	48	18	30	24
330	-	2400	43	50	14	7	10,5	M 10	8,5	218	66	22	37	39,5
430	-	2800	64	58	18	10	12,5	M 12	8,5	268	77,5	26	43	45
530	-	4500	90	77	18	10	12,5	M 12	12,5	337	117,5	32	49	85

Größe		l ₁ ≈		l ₂ ≈	l ₃ max.	l ₄	m ₁	m ₂	m ₃	m ₄	r ≈	s	w
Stahl	Edelstahl	Form B	Form E										Verstellweg
		Form BC											
75	75	66,5	67	31,5	41	45	15	16	5	5	62,5	4	15
130	130	85	86	42	54	55	12,5	19	6,5	7,5	79	5	17,5
230	230	110,5	112	58	73	68	19	20	6,5	6,5	104	6	20
330	-	129	130,5	66	86	77	28,7	32,3	10	9,5	122	7	19
430	-	164	166	88	114	100	32	32	10	10	156	10	33
530	-	223	225	128	155	100	50	51	12,5	12,5	212	10	27