



## 2 Form

- M** offener Spannarm, mit 2 Flankenscheiben
- MC** offener Spannarm, mit 2 Flankenscheiben und Andrückschraube GN 708.1
- O** massiver Spannarm, mit Halteschelle zum Anschweißen

## 1

Größe		F <sub>H</sub> in N	a ≈	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub>	d <sub>1</sub>	d <sub>2</sub>	h <sub>1</sub> ≈	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub>	h <sub>5</sub> max.
Stahl	Edelstahl	Haltekraft											
25*	25*	400	10	24	24,5	4,3	M 4	4,3	23	12	7	13,5	-
75	75	900	20	28	26	5,5	M 5	4,5	37	20	11	19	5
130	130	1000	32	36	40	6,5	M 6	5,5	51	30,5	16	25,5	14
230	230	1700	37	44	42	8,5	M 8	6,5	61,5	36,5	18	30	12,5
355	-	1800	58	60	56	10,4	M 10	8,5	83	50	22	37	23,5
455	-	3200	65	70	65	12,4	M 12	8,5	98,5	60	26	43	27,5

Größe		l <sub>1</sub> ≈	l <sub>2</sub> ≈	l <sub>3</sub> ≈	l <sub>4</sub> max.	l <sub>5</sub>	m <sub>1</sub>	m <sub>2</sub>	m <sub>3</sub>	r	s <sub>1</sub>	s <sub>2</sub>	w Verstellweg
Stahl	Edelstahl												
25*	25*	69	43	20	-	-	15	16	16	24,5	1,2	-	-
75	75	118	67	40	49,5	45	13,5	16	19	43	2	4	15
130	130	168	92	53	64	55	26	22,4	28,4	62	2,5	5	17,5
230	230	196	110	63,5	78	68	26	26	31,5	72	3	6	20
355	-	270	161	96	115	77	41	38,8	43	108,5	3,5	7	19
455	-	309	186	116	135	100	41,5	40	43	126	4	10	33

\* Größe 25 nur in Form M lieferbar