




Verstellbarer Stirnlochschlüssel

für Zweilochmuttern


Spezialstahl, im Brünierten angelassen.



◀ **Nr. 12 109**

Bestellbeispiel:
12109.07-40/1.5


Bereich 07-40
Zapfen 1,5



	*					
7 - 40	1,5			2,8	115	3 40
7 - 40	2		3,6	115	3	40
7 - 40	2,5			4	115	3 40
11 - 60	3		4	160	4	140
11 - 60	4		5	160	4	140
11 - 60	5		6	160	4	140
14 - 100	5		6	215	6	300
14 - 100	6		7	215	6	300
14 - 100	8		8	215	6	300
22 - 125	8		8	260	6	500
22 - 125	10		10	260	6	500
22 - 125	12		12	260	6	500

* Zapfenmaß = Nennmaß -0,1 mm; Toleranzfeld h₁₂.


Auch lieferbar mit auswechselbaren, gehärteten Zapfen
Ausführung AZ Gr. 11-60 und 14-100



Gelenk- Stirnlochschlüssel

für Zweilochmuttern

Spezialstahl, hochkant geschliffen,
im Brünierten angelassen.



◀ **Nr. 12 110**

Bestellbeispiel:
12110.018-40/3


Bereich 018-40
Zapfen 3



	*					
18 - 40	3		4	150	5	90
18 - 40	4		5	150	5	90
40 - 80	4		5	220	6	245
40 - 80	5		6	220	6	245
40 - 80	6		7	220	6	245
80 - 125	6		7	320	8	670
80 - 125	7		7,5	320	8	670
80 - 125	8		8	320	8	670
125 - 200	8		8	450	10	1750
125 - 200	10		10	450	10	1750

* Zapfenmaß = Nennmaß -0,1 mm; Toleranzfeld h₁₂.

Auch lieferbar mit auswechselbaren, gehärteten Zapfen Ausführung AZ.



12