


EH 22760.

Druck- schrauben

mit Messingbolzen



Werkstoff:

Schraube: • Vergütungsstahl, 1200 ± 100 N/mm²
• Rostfreier Stahl 1.4305

Bolzen: • Messing

Hinweis:

Zum schonenden Klemmen oder Andrücken von Gewindespindeln, Achsen, Wellen und oberflächenbehandelten Teilen.

Best.-Nr. Stahl	Best.-Nr. Rostfreier Stahl	d ₁	l ₁	l ₂	d ₂	SW	⌀ g
22760.0042	22760.0442	M 4	6,5	1,2	2,5	2,0	0,3
22760.0044	22760.0444	M 4	10,5	1,2	2,5	2,0	0,8
22760.0046	22760.0446	M 4	16,5	1,2	2,5	2,0	1,2
22760.0052	22760.0452	M 5	8,5	1,3	3,0	2,5	0,9
22760.0054	22760.0454	M 5	12,5	1,3	3,0	2,5	1,4
22760.0056	22760.0456	M 5	20,5	1,3	3,0	2,5	2,1
22760.0062	22760.0462	M 6	11,5	1,9	4,0	3,0	1,7
22760.0064	22760.0464	M 6	17,5	1,9	4,0	3,0	2,7
22760.0066	22760.0466	M 6	26,5	1,9	4,0	3,0	4,2
22760.0082	22760.0482	M 8	12,0	2,5	5,5	4,0	3,0
22760.0086	22760.0486	M 8	22,0	2,5	5,5	4,0	5,8
22760.0088	22760.0488	M 8	32,0	2,5	5,5	4,0	8,9
22760.0102	22760.0502	M 10	14,0	2,7	7,0	5,0	5,6
22760.0104	22760.0504	M 10	18,0	2,7	7,0	5,0	6,7
22760.0106	22760.0506	M 10	27,0	2,7	7,0	5,0	11,0
22760.0108	22760.0508	M 10	37,0	2,7	7,0	5,0	16,0
22760.0122	22760.0522	M 12	18,5	3,4	8,5	6,0	10,0
22760.0124	22760.0524	M 12	22,5	3,4	8,5	6,0	12,0
22760.0126	22760.0526	M 12	32,5	3,4	8,5	6,0	20,0
22760.0128	22760.0528	M 12	42,5	3,4	8,5	6,0	27,0

