



1

2

3

d ₁		d ₂	l ₁				d ₃ ≈	l ₂	sw	Statische Belastbarkeit in kN (Hinweis beachten)	
ST / NI	NV									ST / NI	NV
15	-	M 6	26	36	46	-	4,5	7,6	3	3,5	-
15	-	M 8	20	35	45	58	6,1	7,6	4	3,5	-
18	-	M 6	26	36	46	-	4,5	9,2	3	3,5	-
18	-	M 8	20	35	45	58	6,1	9,2	4	3,5	-
18	-	M 10	34	44	57	74	7,8	9,2	5	3,5	-
21	21	M 6	26	36	46	-	4,5	10	3	3,5	3,5
21	21	M 8	20	35	45	58	6,1	10	4	3,5	7
21	21	M 10	34	44	57	74	7,8	10	5	3,5	11
21	21	M 12	34	57	74	94	9,4	10	6	3,5	16
25	25	M 6	26	36	46	-	4,5	10,5	3	3,5	3,5
25	25	M 8	20	35	45	58	6,1	10,5	4	3,5	7
25	25	M 10	34	44	57	74	7,8	10,5	5	3,5	11
25	25	M 12	34	57	74	94	9,4	10,5	6	3,5	16
32	32	M 6	26	36	46	-	4,5	11	3	3,5	3,5
32	32	M 8	20	35	45	58	6,1	11	4	3,5	7
32	32	M 10	34	44	57	74	7,8	11	5	3,5	11
32	32	M 12	34	57	74	94	9,4	11	6	3,5	16
40	40	M 8	20	35	45	58	6,1	13	4	3,5	7
40	40	M 10	34	44	57	74	7,8	13	5	3,5	11
40	40	M 12	34	57	74	94	9,4	13	6	3,5	16