



EH 24450.

**Feste
Ballengriffe**
DIN 39



Werkstoff:
• Stahl, gedreht, galvanisch verzinkt, passiviert

| Best.-Nr. | Ausführung | d ₁ | d ₂ h8 | d ₃ | d ₄ h13 | l ₁ ≈ | l ₂ | l ₃ | SW | g |
|------------|---------------------|----------------|----------------------|----------------|-----------------------|---------------------|----------------|----------------|----|-----|
| 24450.0016 | mit glattem Zapfen, | 16 | 7 | – | 10 | 50 | 11 | 7 | – | 45 |
| 24450.0020 | Form D | 20 | 8 | – | 13 | 64 | 13 | 8 | – | 92 |
| 24450.0025 | (Bild 1) | 25 | 10 | – | 16 | 80 | 14 | 10 | – | 177 |
| 24450.0032 | | 32 | 13 | – | 20 | 100 | 21 | 13 | – | 359 |
| 24450.0036 | | 36 | 16 | – | 22 | 112 | 26 | 14 | – | 519 |
| 24450.0116 | mit Gewindepapfen, | 16 | – | M 6 | 10 | 50 | 11 | 7 | 3 | 43 |
| 24450.0120 | Form E | 20 | – | M 8 | 13 | 64 | 13 | 8 | 4 | 88 |
| 24450.0125 | (Bild 2) | 25 | – | M 10 | 16 | 80 | 14 | 10 | 5 | 175 |
| 24450.0132 | | 32 | – | M 12 | 20 | 100 | 21 | 13 | 6 | 346 |
| 24450.0136 | | 36 | – | M 16 | 22 | 112 | 26 | 14 | 8 | 509 |

