

Fortsetzung von vorheriger Seite

EH 22720.

Best.-Nr. Stahl, vergütet	Best.-Nr. Rostfreier Stahl	Ausführung	d ₁	l ₂	d ₃	Kugel	SW	Belastbarkeit bei statischer Belastung max. kN*	g
22720.0702	-	Auflagefläche plan	M 20	30,0	13,5	15,0	10,0	90,0	49,00
22720.0704	-		M 20	40,0	13,5	15,0	10,0	90,0	70,00
22720.0705	-		M 20	50,0	13,5	15,0	10,0	90,0	90,00
22720.0706	-		M 20	60,0	13,5	15,0	10,0	90,0	111,00
22720.0742	-		M 24	35,0	15,8	18,0	12,0	120,0	86,00
22720.0744	-		M 24	50,0	15,8	18,0	12,0	120,0	128,00
22720.0746	-		M 24	80,0	15,8	18,0	12,0	120,0	219,00
22720.0891	-	Auflagefläche geriffelt	M 8	10,0	4,5	5,5	4,0	15,0	2,80
22720.0892	-		M 8	12,0	4,5	5,5	4,0	15,0	2,70
22720.0893	-		M 8	16,0	4,5	5,5	4,0	15,0	3,90
22720.0894	-		M 8	20,0	4,5	5,5	4,0	15,0	5,10
22720.0895	-		M 8	25,0	4,5	5,5	4,0	15,0	6,60
22720.0896	-		M 8	30,0	4,5	5,5	4,0	15,0	8,10
22720.0901	-		M 10	12,0	6,0	7,0	5,0	20,0	4,70
22720.0902	-		M 10	16,0	6,0	7,0	5,0	20,0	5,80
22720.0903	-		M 10	20,0	6,0	7,0	5,0	20,0	7,70
22720.0904	-		M 10	25,0	6,0	7,0	5,0	20,0	10,00
22720.0905	-		M 10	30,0	6,0	7,0	5,0	20,0	13,00
22720.0906	-		M 10	35,0	6,0	7,0	5,0	20,0	15,00
22720.0908	-		M 10	40,0	6,0	7,0	5,0	20,0	17,00
22720.0921	-		M 12	16,0	7,2	8,5	6,0	30,0	8,60
22720.0922	-		M 12	20,0	7,2	8,5	6,0	30,0	11,00
22720.0923	-		M 12	25,0	7,2	8,5	6,0	30,0	14,00
22720.0924	-		M 12	30,0	7,2	8,5	6,0	30,0	18,00
22720.0926	-		M 12	40,0	7,2	8,5	6,0	30,0	25,00
22720.0928	-		M 12	50,0	7,2	8,5	6,0	30,0	32,00
22720.0961	-		M 16	20,0	10,7	12,0	8,0	60,0	21,00
22720.0962	-		M 16	25,0	10,7	12,0	8,0	60,0	26,00
22720.0964	-		M 16	35,0	10,7	12,0	8,0	60,0	40,00
22720.0966	-		M 16	50,0	10,7	12,0	8,0	60,0	60,00
22720.0972	-		M 20	30,0	13,5	15,0	10,0	90,0	50,00
22720.0974	-		M 20	40,0	13,5	15,0	10,0	90,0	70,00
22720.0975	-		M 20	50,0	13,5	15,0	10,0	90,0	89,00
22720.0976	-		M 20	60,0	13,5	15,0	10,0	90,0	111,00
22720.0982	-		M 24	35,0	15,8	18,0	12,0	120,0	84,00
22720.0984	-		M 24	50,0	15,8	18,0	12,0	120,0	125,00
22720.0986	-		M 24	80,0	15,8	18,0	12,0	120,0	219,00
22720.0452	22720.0492	abgeflachte Kugel	M 4	5,9	1,8	2,5	2,0	0,3	0,24
22720.0453	22720.0493	aus Thermoplast,	M 4	7,9	1,8	2,5	2,0	0,3	0,35
22720.0454	22720.0494	Auflagefläche plan	M 4	9,9	1,8	2,5	2,0	0,3	0,49
22720.0455	22720.0495	(verdrehgesichert)	M 4	11,9	1,8	2,5	2,0	0,3	0,88
22720.0456	22720.0496		M 4	15,9	1,8	2,5	2,0	0,3	0,92
22720.0462	22720.0502		M 5	7,8	2,1	3,0	2,5	0,5	0,80
22720.0463	22720.0503		M 5	9,8	2,1	3,0	2,5	0,5	0,74
22720.0464	22720.0504		M 5	11,8	2,1	3,0	2,5	0,5	1,23
22720.0465	22720.0505		M 5	15,8	2,1	3,0	2,5	0,5	1,40
22720.0466	22720.0506		M 5	19,8	2,1	3,0	2,5	0,5	2,00
22720.0467	22720.0507		M 5	24,8	2,1	3,0	2,5	0,5	2,70
22720.0472	22720.0512		M 6	10,3	3,0	4,0	3,0	0,9	1,10
22720.0473	22720.0513		M 6	12,3	3,0	4,0	3,0	0,9	1,70
22720.0474	22720.0514		M 6	16,3	3,0	4,0	3,0	0,9	2,10
22720.0475	22720.0515		M 6	20,3	3,0	4,0	3,0	0,9	2,76
22720.0476	22720.0516		M 6	25,3	3,0	4,0	3,0	0,9	3,60
22720.0482	22720.0522		M 8	10,4	4,2	5,5	4,0	1,5	1,80
22720.0483	22720.0523		M 8	12,4	4,2	5,5	4,0	1,5	2,20
22720.0484	22720.0524		M 8	16,4	4,2	5,5	4,0	1,5	3,40
22720.0485	22720.0525		M 8	20,4	4,2	5,5	4,0	1,5	4,80
22720.0486	22720.0526		M 8	25,4	4,2	5,5	4,0	1,5	6,10
22720.0487	22720.0527		M 8	30,4	4,2	5,5	4,0	1,5	7,60

* Belastbarkeitsangaben gelten nicht für Ausführung aus rostfreiem Stahl (ausgenommen bei Ausführung mit Thermoplast-Kugel).

Kugeldruckschrauben

ohne Kopf, abgeflachte Kugel

