

Fortsetzung von vorheriger Seite

EH 22150.

Best.-Nr.	Ausführung	d ₁	l ₁ -1,5	Federkraft F max. N≈*	d ₂	l ₂	s +/-	SW	g
22150.0370	Thermoplaststift, ohne Abdichtung	M 12	11,5	20	5	6,7	0,8	10	2,7
22150.0373		M 12	11,5	40	6	10,7	1,0	10	3,1
22150.0375		M 12	19,0	20	5	6,7	0,8	10	4,6
22150.0380		M 12	19,0	40	6	10,7	1,0	10	4,8
22150.0383		M 12	26,5	20	5	6,7	0,8	10	6,5
22150.0385		M 12	26,5	40	6	10,7	1,0	10	6,8
22150.0390		M 18 x 1,5	18,0	100	10	16,7	1,6	16	12,0
22150.0393		M 18 x 1,5	31,5	100	10	16,7	1,6	16	20,0
22150.0395		M 18 x 1,5	45,0	100	10	16,7	1,6	16	30,0

Seiten- druckstücke

mit Gewinde,
ohne Abdichtung



Best.-Nr.	Ausführung	d ₁	g
22150.0820	Montagewerkzeug 	M 12	76
22150.0822		M 18 x 1,5	137

* statistischer Mittelwert

