

EH 24580.

Fortsetzung von vorheriger Seite

Handräder

DIN 950

Grauguss



Best.-Nr. d ₂ klein	Best.-Nr. d ₂ groß	Ausführung	d ₁	d ₂ H7 klein	d ₂ H7 groß	d ₃	l ₁ ≈	l ₂	Anzahl der Arme	zugehöriger Ballengriff DIN 39/ DIN 98	g
24580.0400	24580.0401	ohne Nabennut,	80	10	12	24	29	16	3	16	410
24580.0405	24580.0406	mit festem Griff	100	10	12	26	33	17	3	16	550
24580.0410	24580.0411	EH 24450., montiert,	125	12	14	28	36	18	3	20	835
24580.0415	24580.0416	Form B-F/G	140	14	16	30	39	19	3	20	1025
24580.0420	24580.0421	(alt: F 4)	160	14	16	32	40	20	3	25	1380
24580.0430	24580.0431		200	18	22	38	45	24	3	25	2180
24580.0440	24580.0441		250	22	26	45	50	28	5	32	4160
24580.0445	24580.0446		315	26	30	53	56	33	5	32	6160
24580.0450	24580.0451		400	30	34	65	63	38	5	36	10460
24580.0500	24580.0501	mit Nabennut,	80	10	12	24	29	16	3	16	410
24580.0505	24580.0506	mit festem Griff	100	10	12	26	33	17	3	16	550
24580.0510	24580.0511	EH 24450., montiert,	125	12	14	28	36	18	3	20	835
24580.0515	24580.0516	Form N-F/G	140	14	16	30	39	19	3	20	1025
24580.0520	24580.0521	(alt: F 3)	160	14	16	32	40	20	3	25	1380
24580.0530	24580.0531		200	18	22	38	45	24	3	25	2180
24580.0540	24580.0541		250	22	26	45	50	28	5	32	4160
24580.0545	24580.0546		315	26	30	53	56	33	5	32	6160
24580.0550	24580.0551		400	30	34	65	63	38	5	36	10460

Nabennuten DIN 6885 Blatt 1

d ₂	10,0	12,0	14,0	16,0	18,0	22,0	26,0	30,0	34,0
b ₃	3,0	4,0	5,0	5,0	6,0	6,0	8,0	8,0	10,0
t	11,4	13,8	16,3	18,3	20,8	24,8	29,3	33,3	37,3

