

Anschlagwinkel, gehärtet 0390



DIN
875

Ausführung

- mit starkem und schwachem Schenkel
- DIN 875
- **Genauigkeit: GG 0**
- ohne Haarmesskante
- Verpackung: Karton



			Schenkellänge mm	starker Schenkel mm	schwacher Schenkel mm	Best. Nr.
Spezialstahl:						
▪			50 x 40	14 x 10	16 x 2	0390 102
▪			75 x 50	14 x 10	18 x 2	0390 103
▪			100 x 70	16 x 10	18 x 2	0390 104
▪			150 x 100	20 x 12	22 x 3	0390 105
▪			200 x 130	24 x 14	26 x 3	0390 106
▪			300 x 200	30 x 18	32 x 3	0390 108
rostfreier Stahl:						
▪			50 x 40	14 x 10	16 x 2	0390 202
▪			75 x 50	14 x 10	18 x 2	0390 203
▪			100 x 70	16 x 10	18 x 2	0390 204
▪			150 x 100	20 x 12	22 x 3	0390 205
▪			200 x 130	24 x 14	26 x 3	0390 206
▪			300 x 200	30 x 18	32 x 3	0390 208

Anschlagwinkel, gehärtet 0391



DIN
875

Ausführung

- mit starkem und schwachem Schenkel
- mit Haarmesskante
- DIN 875
- **Genauigkeit: GG 00**
- Verpackung: Karton



			Schenkellänge mm	starker Schenkel mm	schwacher Schenkel mm	Best. Nr.
Spezialstahl, mit blendfreier Haarmesskante:						
▪			50 x 40	14 x 10	16 x 2	0391 102
▪			75 x 50	14 x 10	18 x 2	0391 103
▪			100 x 70	16 x 10	18 x 2	0391 104
▪			150 x 100	20 x 12	22 x 3	0391 105
▪			200 x 130	24 x 14	26 x 3	0391 106
▪			300 x 200	30 x 18	32 x 3	0391 108
rostfreier Stahl:						
▪			50 x 40	14 x 10	16 x 2	0391 202
▪			75 x 50	14 x 10	18 x 2	0391 203
▪			100 x 70	16 x 10	18 x 2	0391 204
▪			150 x 100	20 x 12	22 x 3	0391 205
▪			200 x 130	24 x 14	26 x 3	0391 206
▪			300 x 200	30 x 18	32 x 3	0391 208